

Designation	Principal dimensions (mm)			Basic load ratings (KN)		Speed ratings (rpm)		Weight (kg)
	d	D	B	dyc	stc	Speed Ratings	Limiting Speed	
				Cr	Cor			
NCF3004CV	20	42	16	28,1	28,5	8500	10000	0,11
NCF3005CV	25	47	16	31,9	35,5	7000	9000	0,12
NCF3006CV	30	55	19	39,6	44	6000	7500	0,20
NCF3007CV	35	62	20	48,4	56	5300	6700	0,26
NCF3008CV	40	68	21	57,2	69,5	4800	6000	0,31
NCF3009CV	45	75	23	60,5	78	4300	5300	0,40
NCF3010CV	50	80	23	76,5	98	4000	5000	0,43
NCF3011CV	55	90	26	105	140	3400	4300	0,64
NCF2912CV	60	85	16	55	80	3600	4500	0,29
NCF3012CV	60	95	26	106	146	3400	4000	0,69
NCF2913CV	65	90	16	58,3	88	3200	4000	0,31
NCF3013CV	65	100	26	112	163	3000	3800	0,73
NCF2914CV	70	100	19	76,5	116	3000	3800	0,49
NCF3014CV	70	110	30	128	173	2800	3600	1,02
NCF2915CV	75	105	19	79,2	125	2800	3600	0,52
NCF3015CV	75	115	30	134	190	2600	3200	1,06
NCF2916CV	80	110	19	80,9	132	2600	3400	0,55
NCF3016CV	80	125	34	165	228	2400	3000	1,43
NCF2917CV	85	120	22	102	166	2600	3200	0,81
NCF3017CV	85	130	34	172	236	2400	3000	1,51
NCF2918CV	90	125	22	105	176	2400	3000	0,84
NCF3018CV	90	140	37	198	280	2200	2800	1,97
NCF2920CV	100	140	24	128	200	2200	2600	1,14
NCF3020CV	100	150	37	209	310	2000	2600	2,15
NCF2922CV	110	150	24	134	220	1900	2400	1,23
NCF3022CV	110	170	45	275	400	1800	2200	3,50
NCF2924CV	120	165	27	172	290	1800	2200	1,73
NCF3024CV	120	180	46	292	440	1700	2000	3,80
NCF2224V	120	215	58	512	735	1400	1700	9,05
NCF2926CV	130	180	30	205	360	1600	2000	2,33
NCF3026CV	130	200	52	413	620	1500	1900	5,80
NCF2928CV	140	190	30	220	390	1500	1900	2,42
NCF3028CV	140	210	53	440	680	1400	1800	6,10
NCF2228V	140	250	68	693	1020	1200	1500	14,5
NCF2930CV	150	210	36	292	490	1400	1700	3,77
NCF3030CV	150	225	56	457	710	1300	1600	7,50
NCF2230V	150	270	73	792	1180	1100	1400	18,4
NCF3032CV	160	240	60	512	800	1200	1500	9,10
NCF2232V	160	290	80	990	1500	950	1200	23,0
NCF2934CV	170	230	36	314	560	1200	1500	4,30
NCF3034CV	170	260	67	671	1060	1100	1400	12,5
NCF2234V	170	310	86	1100	1700	900	1100	28,7
NCF2936CV	180	250	42	391	695	1100	1400	6,20
NCF3036CV	180	280	74	781	1250	1100	1300	16,5
NCF2938CV	190	260	42	440	780	1100	1400	6,50
NCF3038CV	190	290	75	792	1290	1000	1300	17,0
NCF2238V	190	340	92	1250	1900	800	1000	35,7
NCF1840V	200	250	24	176	335	1100	1400	2,60
NCF2940CV	200	280	48	528	965	1000	1300	9,10
NCF3040CV	200	310	82	913	1530	950	1200	22,5
NCF1844V	220	270	24	183	365	1000	1200	2,85
NCF2944CV	220	300	48	550	1060	950	1200	9,90
NCF3044CV	220	340	90	1080	1800	850	1100	29,5
NCF2244V	220	400	108	1830	2750	700	850	58,0
NCF1848V	240	300	28	260	510	900	1100	4,40
NCF2948CV	240	320	48	583	1140	850	1100	10,6
NCF3048CV	240	360	92	1140	1960	800	1000	32,0

NCF1852V	260	320	28	270	550	800	1000	4,75
NCF2952CV	260	360	60	737	1430	750	950	18,5
NCF3052CV	260	400	104	1540	2550	700	900	46,5
NCF2956CV	280	380	60	880	1730	700	900	19,7
NCF3056CV	280	420	106	1570	2650	670	850	50,0
NCF1860V	300	380	38	418	850	670	850	10,0
NCF2960CV	300	420	72	1120	2200	670	800	31,2
NCF3060CV	300	460	118	1900	3250	600	750	69,0
NCF1864V	320	400	38	440	900	630	800	10,5
NCF2964CV	320	440	72	1140	2360	600	750	32,9
NCF3064CV	320	480	121	1980	3450	560	700	74,5
NCF1868V	340	420	38	446	950	600	750	11,0
NCF2968CV	340	460	72	1190	2500	560	700	35,0
NCF3068CV	340	520	133	2380	4150	530	670	100
NCF1872V	360	440	38	402	900	560	700	11,5
NCF2972CV	360	480	72	1230	2600	530	670	36,5
NCF3072CV	360	540	134	2420	4300	500	630	105
NCF1876V	380	480	46	627	1290	530	670	19,5
NCF2976CV	380	520	82	1570	3250	500	630	52,5
NCF3076CV	380	560	135	2510	4550	480	600	110
NCF1880V	400	500	46	627	1340	500	630	20,5
NCF2980CV	400	540	82	1650	3450	480	600	54,5
NCF3080CV	400	600	148	2970	5500	450	560	145
NCF1884V	420	520	46	660	1430	480	600	21,0
NCF2984CV	420	560	82	1650	3600	450	560	57,0
NCF3084CV	420	620	150	3030	5700	430	530	150
NCF1888V	440	540	46	671	1460	450	560	22,0
NCF2888V	440	540	60	1060	2700	450	560	29,0
NCF2988V	440	600	95	2010	4400	430	530	80,5
NCF3088CV	440	650	157	3580	6550	400	500	175
NCF2892V	460	580	72	1300	3050	430	530	44,0
NCF2992V	460	620	95	2050	4500	400	500	83,5
NCF3092CV	460	680	163	3690	6950	380	480	195
NCF1896V	480	600	56	935	2040	400	500	35,5
NCF2896V	480	600	72	1320	3150	400	500	46,0
NCF2996V	480	650	100	2290	4900	380	480	98,0
NCF3096CV	480	700	165	3740	7200	360	450	205
NCF18/500V	500	620	56	952	2120	380	480	36,5
NCF28/500V	500	620	72	1340	3350	380	480	48,0
NCF29/500V	500	670	100	2330	5000	380	450	100
NCF30/500CV	500	720	167	3800	7500	360	450	215
NCF18/530V	530	650	56	990	2240	360	450	38,5
NCF28/530V	530	650	72	1400	3450	360	450	49,5
NCF29/530V	530	710	106	2640	6100	340	430	120
NCF30/530V	530	780	185	5230	10600	320	400	300
NCF18/560V	560	680	56	1020	2360	340	430	40,5
NCF28/560V	560	680	72	1420	3650	340	430	54,0
NCF29/560V	560	750	112	3080	6700	320	400	140
NCF30/560V	560	820	195	5830	11800	300	380	345
NCF18/600V	600	730	60	1050	2550	320	400	51,5
NCF28/600V	600	730	78	1570	4300	320	400	67,5
NCF29/600V	600	800	118	3190	7100	300	380	170
NCF18/630V	630	780	69	1250	2900	300	360	72,5
NCF28/630V	630	780	88	1870	5000	300	360	92,5
NCF29/630V	630	850	128	3740	8650	280	340	205
NCF18/670V	670	820	69	1300	3150	280	340	76,5
NCF28/670V	670	820	88	1940	5300	280	340	97,5
NCF29/670V	670	900	136	3910	9000	260	320	245
NCF28/710V	710	870	95	2330	6300	260	320	115
NCF29/710V	710	950	140	4290	10000	240	300	275
NCF18/750V	750	920	78	1870	4500	240	300	110
NCF28/750V	750	920	100	2640	6950	240	300	140

NCF29/750V	750	1000	145	4460	10600	220	280	315
NCF18/800V	800	980	82	1940	4800	220	280	130
NCF28/800V	800	980	106	2750	7500	220	280	165
NCF29/800V	800	1060	150	4950	12200	200	260	360
NCF18/850V	850	1030	82	2010	5100	200	260	135
NCF28/850V	850	1030	106	2860	8000	200	260	175
NCF29/850V	850	1120	155	5230	12700	190	240	405
NCF18/900V	900	1090	85	2380	6000	190	240	160
NCF28/900V	900	1090	112	3190	9150	190	240	208
NCF29/900V	900	1180	165	5940	14600	170	220	472
NCF18/950V	950	1150	90	2420	6300	170	220	185
NCF28/950V	950	1150	118	3410	9800	170	220	240
NCF29/950V	950	1250	175	6600	16300	160	200	565
NCF18/1000V	1000	1220	100	2920	7500	160	200	230
NCF28/1000V	1000	1220	128	4130	11600	160	200	310
NCF29/1000V	1000	1320	185	7480	18600	150	190	680
NCF18/1120V	1120	1360	106	3740	9650	130	170	298