

Bearing NO.		Boundary dimensions(mm)						Basic load ratings(kN)		Minimum load	Design	Weight(kg)
New	Old	d	D	H	r _{1, 2min}	d _r	D ₁	Ca	Coa	A		Refer
89320	9549320	100	170	42	1.5	170	103	300	1370	0.15	2	4.2
89420	9549420	100	210	67	3	210	103	680	2800	0.63	2	12
89322	9549322	110	190	48	2	190	113	400	1830	0.27	2	6.05
89422	9549422	110	230	73	3	230	113	800	3350	0.9	2	15.5
89324	9549324	120	210	54	2.1	210	123	500	2280	0.42	2	8.5
89424	9549424	120	250	78	4	250	123	930	3900	1.2	2	19.5
89326	9549326	130	225	58	2.1	225	134	560	2650	0.56	2	10
89426	9549426	130	270	85	4	270	134	1060	4500	1.6	2	24
89328	9549328	140	240	60	2.1	240	144	640	3100	0.77	2	12
89428	9549428	140	280	85	4	280	144	1100	4800	1.8	2	27
89330	9549330	150	250	60	2.1	250	154	670	3250	0.85	2	12.5
89430	9549430	150	300	90	4	300	154	1250	5600	2.5	2	32
89332	9549332	160	270	67	3	270	164	780	3800	1.2	2	16.5
89432	9549432	160	320	95	5	320	164	1430	6400	3.3	2	38
89334	9549334	170	280	67	3	280	174	800	4000	1.3	2	17.5
89434	9549434	170	340	103	5	340	174	1600	7200	4.1	2	47
89336	9549336	180	300	73	5	300	184	1020	5000	2	2	22
89436	9549436	180	360	109	5	360	186	1900	7200	5.8	1	56.5
89338	9549338	190	320	78	4	320	195	1140	5600	2.5	2	27
89340	9549340	200	340	85	4	340	205	1290	6400	3.3	2	32
89344	9549344	220	360	85	4	360	220	1210	5450	4.1	2	36.9
89444	9549444	220	420	112	6	420	225	2320	11200	10	2	82
89348	9549348	240	400	85	4	380	240	1290	6100	5.8	2	39.4
89352	9549352	260	420	95	1.1	420	260	1670	7700	8.7	2	55.2
89452	9549452	260	480	132	6	480	265	2850	14300	16	2	114
89356	9549356	280	440	95	5	438	282	1800	8650	8.7	2	58.4
89160	9549160	300	380	48	2	377	303	640	3550	1	1	13.5
89360	9549360	300	480	109	5	480	300	2260	10500	6.7	2	81.7
89364	9549364	320	500	109	5	500	325	2200	10400	6.7	2	85.9
89368	9549368	340	540	122	5	540	345	2790	13300	8.7	2	115
89172	9549172	360	440	48	2	437	363	680	4150	1.4	1	15.5
89372	9549372	360	560	122	5	560	360	2870	14000	8.7	2	120
89176	9549176	380	460	48	2	457	383	710	4400	1.5	1	16.5
89180	9549180	400	480	48	2	477	403	735	4650	1.7	1	17.5
89480	9549480	400	710	185	7.5	710	405	5700	31000	77	1	350
89184	9549184	420	500	48	2	497	423	765	4900	1.9	1	18
89188	9549188	440	540	60	2.1	537	443	1040	6400	3.3	1	30
89192	9549192	460	560	60	2.1	557	463	1080	6700	3.6	1	31.5
89196	9549196	480	580	60	2.1	577	483	1100	6950	3.9	1	32.5
891500	95491500	500	600	60	2.1	597	503	1220	8150	5.3	1	34
891530	95491530	530	640	67	3	636	534	1370	8800	6.2	1	44
891560	95491560	560	670	67	3	666	564	1370	9150	6.7	1	46.5
891600	95491600	600	710	67	3	706	604	1430	9650	7.4	1	49.5
891630	95491630	630	750	73	3	746	634	1630	11200	10	1	62
891670	95491670	670	800	78	4	795	675	2000	13400	14	1	75.5
891710	95491710	710	850	85	4	845	715	2200	15000	18	1	95
891750	95491750	750	900	90	4	895	755	2400	16600	22	1	115
891800	95491800	800	950	90	4	945	805	2500	18000	26	1	120
891850	95491850	850	1000	90	4	995	955	2600	19000	29	1	130
891900	95491900	900	1060	95	5	1055	905	3050	22000	39	1	150
891950	95491950	950	1120	103	5	1115	955	3450	25000	50	1	185
8911000	954911000	1000	1180	109	5	1175	1005	3900	28500	65	1	220
8911060	954911060	1060	1250	115	5	1245	1065	4150	31000	77	1	260
8911120	954911120	1120	1320	122	5	1315	1125	4900	36500	110	1	305