

Bearing Number	Basic dimension (mm)			Load (kN)		ltd. speed (rpm)		Weight
	d	D	B	Cr	Cor	Grease	Oil	Kg
16100	10	28	8	5.1	2.4	20000	26000	0.022
16000	10	26	7	5.1	2.4	20000	26000	0.022
16001	12	28	7	5.1	2.4	20000	26000	0.015
16002	15	32	8	5.6	2.8	19000	24000	0.023
16003	17	35	8	6	3.3	18000	22000	0.028
16004	20	42	8	7.9	4.5	16000	19000	0.052
16005	25	47	8	8.8	5.6	13000	17000	0.059
16006	30	55	9	11.2	7.4	11000	14000	0.084
16007	35	62	9	12.2	8.8	9500	12000	0.107
16008	40	68	9	12.6	9.6	9000	11000	0.125
16009	45	75	10	15.6	12.2	8000	10000	0.155
16010	50	80	10	16.1	13.1	8000	9500	0.166
16011	55	90	11	19.4	16.2	7000	8500	0.207
16012	60	95	11	19.9	17.5	6300	7500	0.224
16013	65	100	11	20.5	18.6	6000	7000	0.241
16014	70	110	13	27.9	25	5600	6700	0.386
16015	75	115	13	28.7	26.8	5300	6300	0.411
16016	80	125	14	33.1	31.4	5000	6000	0.539
16017	85	130	14	34	33.3	4500	5600	0.968
16018	90	140	16	41.5	39.3	4300	5300	0.671
16019	95	145	16	42.7	41.9	4000	5000	0.71
16020	100	150	16	43.8	44.3	3800	4800	0.74
16021	105	160	18	51.8	50.6	3600	4500	1
16022	110	170	19	57.4	56.7	3400	4300	1.27
16024	120	180	19	58.8	60.4	3000	3800	1.374
16026	130	200	22	79.7	79.2	2800	3600	1.868
16028	140	210	22	82.1	85	2400	3200	2
16030	150	225	24	91.9	98.5	2200	3000	2.638
16032	160	240	25	98.7	107	2000	2800	2.835
16034	170	260	28	118	130	1900	2600	4.157
16036	180	280	31	144	157	1800	2400	5.135
16038	190	290	31	149	168	1700	2200	5.429
16040	200	310	34	167	191	1800	2000	6.624
16044	220	340	37	181	216	1400	1800	9.285
16048	240	360	37	172	210	1200	1600	14.5
16052	260	400	44	235	310	1100	1500	22.5
16056	280	420	44					
16060	300	460	50					
16064	320	480	50					
16068	340	520	57					
16072	360	540	57					
16052	260	400	44					
16052	260	400	44	235	310	1100	1500	23
16052M	260	400	44	235	310	1100	1500	25
16056	280	420	44	235	330	1300	1600	22.5
16056M	280	420	44	235	330	1300	1600	24.8
16060	300	460	50	289	400	1200	1500	31.5
16060	300	460	50	289	400	1200	1500	36.4
16064	320	480	50	275	400	1100	1300	34
16064M	320	400	50	275	400	1100	1300	37.4
16068	340	520	57	335	520	950	1200	46
16068	340	520	57	335	520	950	1200	50.6
16072	360	540	57	340	540	1000	1200	50
16072M	360	540	57	340	540	1000	1200	55
16076	380	560	57	368	615	940	1100	50
16076	380	560	57	368	615	1100	6500	6